

Teleprompter Freestand

Perfect reading, unlimited movement

TVPROMPT



- Lightweight teleprompter thanks to its aluminum structure.
- Designed for reading from up to 5.5 meters away.
- E-IMAGE EG10C/C2 tripod
- E-IMAGE 7004 dolly

Specifications Teleprompter

- Connections: VGA, HDMI, CVBS PAL in-out loop, and HD/SDI in-out loop inputs.
- Brightness: standard/1000/1500 Nits.
- Aspect ratio: 4:3.
- Native resolution: 1024 x 768 px.
- Allows inversion via software (mirror image included in the hardware in mirror versions).
- Electrical voltage: 12V DC, AC adapter 100-240V, 50-60Hz.
- Glass dimensions: 349 x 322 mm.
- Glass thickness: 3 mm.
- Weight of 15" TFT flat screen display unit: 4 kg.
- Weight of visor with semi-reflective glass: 1.1 kg.
- Warranty: 2 years.

Specifications Tripod

- Carbon fiber tripod.
- 75 mm ball head.
- Supports up to 10 kg.
- Working height 780-1700 mm.
- Includes carrying bag.

Specifications Dolly

- Payload - 60kg.
- Working diameter - 950mm.
- Individual brakes.
- Folds for transport.
- Net weight - 3.2kg.

Versions

- Freestand 15": standard, 1000 Nits, 1500 Nits.
- Freestand 17": standard, 1000 Nits, 1500 Nits.
- Freestand 19": standard, 1000 Nits, 1500 Nits.
- Freestand 22": standard, 1000 Nits, 1500 Nits.

Our Software



TVPROMPT LE | For conferences, training centers, and local TV stations.



TVPROMPT XPRO | For political campaigns, speeches, producers, singers, and professional TV studios.