

Teleprompter **STUDIO 32"**

TVPROMPT

With aluminum structure and tilting head

Specifications

- **32" Teleprompter**, designed for a reading of **15 m approximately**.
- **Horizontal movement with fixation** on monitor, head and camera.
- **32" TFT monitor** | Resolution until 1920 x 1080 px.
- **Power supply:** 12 V DC; adapter 100-240 V AC, 50-60 Hz.
- **Mirror version:** monitor with image inversion and direct output.
- **Aspect ratios:** 4:3 / 16:9 / 16:10 / 2.35:1 / 2:1 / 1:1.
- **Inputs:** VGA, HDMI, PAL.
- **Support plate** for professional cameras.
- **Anti-light fabric filter.**
- **Polarized and ultra-clear glass.**
- **Autobalance.**
- **Weight:** 15 Kg.
- **Brightness:** 300/1.000/1.500 Nits.



Our Software



TVPROMPT LE | For conferences, training centers and local TV stations.



TVPROMPT XPRO | For political campaigns, speeches, producers, singers and professional TV studios.



TVPROMPT MOS | For integration with NEWS-NRCS news systems and TV studios.



TVPROMPT iPRO | For integration with AVID iNEWS in TV studios.

What's included?

- **Metallic structure.**
- **Head with glass and support.**
- **32" monitor with support.**
- **Support-plate** for professional cameras.
- **Filter-cloth opacity 100%**
- **Warranty: 2 years.**

Versions

- **Standard (300 Nits) + Mirror**
- **High Brightness (1.000 Nits)**
- **Ultra High Brightness (1.500 Nits)**