

Teleprompter Lightweight 15"

With aluminum frame and head

TVPROMPT

**It is characterized by its portability and low weight
(5.1 kg)**



- Lightweight teleprompter thanks to its aluminum structure.
- Designed for a reading distance of up to 5.5 meters.

Specifications

- Connections: VGA, HDMI, CVBS PAL in-out loop and HD/SDI in-out loop inputs.
- Brightness: 350 Nits | 1.000 Nits | 1.500 Nits
- Aspect ratio: 4:3.
- Native resolution: 1024 x768 px
- Allows inversion through software (mirror image included in hardware in mirror versions).
- Electrical voltage: 12V DC, AC adapter 100-240V, 50-60Hz.
- Glass dimensions: 349 x 322 mm.
- Glass thickness: 3 mm.
- Weight of 15" TFT flat panel display unit: 4kg.
- Weight of visor with semi-reflective glass: 1.1 kg.
- Warranty: 2 years.

Versions

- Standard + mirror (350 Nits).
- High Brightness 1 + mirror (1.000 Nits).
- High Brightness 2 + mirror (1.500 Nits).

What's included?

- Metallic structure.
- Head with glass and support.
- Support-plate for professional cameras.
- Filter-cloth 100% opacity.
- 15" monitor with support.

Our Software



TVPROMPT LE | For conferences, training centers and local TV stations.



TVPROMPT XPRO | For political campaigns, speeches, producers, singers and professional TV studios.