Confer-Prompt **BASIC**

Individual teleprompter for conferences and rallies

Specifications

- Aluminum structure.
- 17" TFT-LDC monitor: 450 Nits brightness.
- **Resolution:** 1920 x 1080.
- Aspect ratio: 4:3 / 16:9 / 16:10 / 2.35:1 / 2:1 / 1:1.
- · Image inversion and direct output.
- Power supply 12 V DC, adapter 100-240 V AC, 50-60Hz.
- VGA, HDMI, CVBS PAL and HD/SDI inputs.
- Black metal telescopic mast for height adjustment (up to 2m. with the whole system mounted).
- Metal support for glass, adjustable in angle.
- Ultra-transparent polarized glass, 70/30 beam splitter and high precision for mirror image.
- 360° rotation of the glass support.
- Custom size.
- Glass thickness: 3 mm.
- System weight: 7 kg.
- Warranty: 2 years.

What's included?

- · Metallic structure with floor support.
- 17" TFT monitor.
- · Black metal telescopic mast for height adjustment.
- Flexo to regulate the position of the
- Metallic support for glass, adjustable in angle.
- Ultra-transparent polarized glass, beam splitter 70/30 and high precision.
- · Bag for extensible support.

The Basic Conference Teleprompter is a practical, lightweight and easy to assemble solution that allows you to read speeches while maintaining eye contact with the audience, ideal for professional presentations.



TFT 17" Monitor



Our Software





TVPROMPT XPRO | For political campaigns, speeches, producers, singers and professional TV studios.





